

Roka Backer Rod

A Polyethylene Based Backing Rod

Roka Backer Rod is a closed cell, extruded polyethylene foam backing rod, used as a backing material for different sealants to give the correct thickness.

Uses & Advantages:

- Easy to apply.
- Does not bond to most sealants.
- Compatible with cold applied sealants.
- Good temperature resistance.
- Good water resistance.
- Highly flexible and compressible.

Technical Information:

Color	Black / White
Chemical Base	Extruded Polyethylene Foam
Service Temperature	-40°C to +70°C
Chemical Resistance	Good resistance to solvents, oil and petrol
Shelf Life	Unlimited if stored in recommended conditions















Storage Conditions

Keep in dry conditions, in a shaded and cool area

& protect from direct sunlight

Application:

Roka Backer Rod's diameter should be approximately 20 to 30% larger than the joint width. During application, it is important to avoid any excessive longitudinal stretching of the rod. During application, be careful not to cut or puncture the surface skin.

Roka Backer Rod must not be used where sealant is heated and applied at a temperature above +70° C.

Important Note:

The information provided in this data sheet is based on ongoing development efforts and extensive field experience. While we strive to ensure the accuracy and reliability of the information, we cannot assume responsibility for any work performed using our materials, as we have no control over application methods, site conditions, and other factors. Due to ongoing research and development in our laboratories, we recommend that customers verify that this data sheet has not been replaced by a more recent publication.













All products are sold under our standard conditions of sale, which are available upon request.

Any field services offered do not imply supervisory responsibility. For further information, please

contact your local representative of Roka Chem Solutions.











