



Roka EP Thinner

Heavy Duty Epoxy Thinner

Roka EP Thinner is a blend of solvents formulated for use as an epoxy thinner.

Uses & Advantages:

- Ideal for epoxy primers.
- Compatible with film forming paint products.
- Used to avoid cobwebbing i.e. the coating drying as it leaves the spray gun.
- As a cleaning agent.

Technical Information:

Color	Clear
Dosage	Depends on the epoxy coating being used
Density	0.88±0.2 kg/l
Flash Point	25°C
VOC	100%
Grade Point	Slow Thinner
Packaging	1, 4 and 200 liters
Shelf life	12 months if kept in recommended conditions



+92 321 4543320



info@rokachemsolutions.com



rokachemsolutions.com



83 A, Block C, PAF Colony, Zarar
Shaheed Road, Lahore Cantt, Pakistan



Storage

Store in a dry, cool area in unopened and undamaged packaging, between 10 to 25°C and away from direct sunlight.

Mixing:

Gradually add Roka EP Thinner, depending on the epoxy being used (generally 5 to 15%). The thinned solution should be stirred thoroughly and allowed to stand for 10 minutes. All air bubbles must be allowed time to disperse before use.

Safety Measures:

- Roka EP Thinner is highly flammable. Eliminate all sources of ignition in and around the working area.
- Do not smoke in or around the working area.
- Ensure the working area is well ventilated and avoid inhalation of vapours and spray mist.
- Keep away from food drink and animal feeding stuffs.
- Do not empty into drains.

Color Variation:

Color and gloss retention on topcoats may vary as it depends on the quality of application, generic type of paint, type of color and environmental factors like temperature, UV intensity etc.



+92 321 4543320



info@rokachemsolutions.com



rokachemsolutions.com



83 A, Block C, PAF Colony, Zarar
Shaheed Road, Lahore Cantt, Pakistan



Health and Safety:

Use of protective clothing, safety goggles, gloves and combined organic vapor respirator is recommended while handling Roka EP Thinner. Avoid contact with skin and avoid vapors or mist inhalation. In case of any contact with skin, immediately clean with industrial skin cleanser followed by washing with soap and water. Any splashes in eyes should be cleaned with plenty of clean water and seek medical assistance immediately.

If you have trouble breathing, leave the area to get fresh air. If continued difficulty is experienced, get medical assistance immediately.

Important Note:

The information provided in this data sheet is based on ongoing development efforts and extensive field experience. While we strive to ensure the accuracy and reliability of the information, we cannot assume responsibility for any work performed using our materials, as we have no control over application methods, site conditions, and other factors. Due to ongoing research and development in our laboratories, we recommend that customers verify that this data sheet has not been replaced by a more recent publication.

All products are sold under our standard conditions of sale, which are available upon request. Any field services offered do not imply supervisory responsibility. For further information, please contact your local representative of Roka Chem Solutions.



+92 321 4543320 |



info@rokachemsolutions.com |



rokachemsolutions.com |



83 A, Block C, PAF Colony, Zarar
Shaheed Road, Lahore Cantt, Pakistan